



Technical data sheet

RACER 10W-30

2T- TC

PERFORMANCE LEVELS: Meets and Exceeds

JASO-FB LEVEL, API-TC

Black bulls 2T Racer is premium quality 2 stroke oil. It is suitable for the use with unleaded gasoline also. 2T Racer is formulated with synthetic base oil with advance performance additive technology and special solvents that permits ready mixing with gasoline over a wide temperature range.

Typical Properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE	NA		2T-TC 10W-30
Kinematic Viscosity @40°C	cSt	ASTM D-445	75
Kinematic Viscosity @100°C	cSt	ASTM D-445	10.9
Viscosity Index	NA	ASTM D-2270	135
Sp. Gravity @ 15 °C/ 60°F	g/cm ³	ASTM D-4052	0.8650
Flash Point (Min)	°C	ASTM D-92	134
Pour Point (Max)	°C	ASTM D-97	-30

Advantages

- Environmental friendly lubricant with reduction of smoke exhaust emissions.
- Avoids carbon deposits in the exhaust system and keeps all the engine power.
- Perfectly adapted to unleaded fuel and new alternative potassium gasoline.
- Very good anticorrosion, antirust and anti-wear properties.
- Quality lubricant adapted to regular scooter use.
- Optimal start-up enabling regular use and a comfortable drive. Its viscosity protects the engine immediately.

