



Technical data sheet

RACER SAE 30

2T- TC

PERFORMANCE LEVELS: Meets and Exceeds

JASO-FB LEVEL, API-TC

Black bulls 2T Racer is premium quality 2 stroke oil. It is suitable for the use with unleaded gasoline also. 2T Racer is formulated with high quality mineral base oil with advance performance additive technology and special solvents that permits ready mixing with gasoline over a wide temperature range.

Typical Properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE	NA		2T-TC SAE 30
Kinematic Viscosity @40°C	cSt	ASTM D-445	71
Kinematic Viscosity @100°C	cSt	ASTM D-445	9.3
Viscosity Index	NA	ASTM D-2270	108
Sp. Gravity @ 15 °C/ 60°F	g/cm ³	ASTM D-4052	0.8800
Flash Point (Min)	°C	ASTM D-92	236
Pour Point (Max)	°C	ASTM D-97	-27

Advantages:

- Makes a permanent oil film, preventing any risk of seizure or binding.
- Avoids ring Sticking.
- Perfectly adapted to unleaded fuel.
- Lubricants guaranteeing multi-faceted protection of the engine.
- Improved cold starting for daily use.
- Very good anticorrosion, antirust and anti-wear properties.
- Avoid sparks plug fouling.
- Burns without leaving any sticky deposits.
- Prediluted to ensure a stable and homogeneous mixture.

