



## AUTOMATIC TRANSMISSION FLUID

### ATF DEXRON VI

#### Performance Profile:

GM DEXRON VI, MAN 339Z-1, V-1, FORD WSS-M2C922-A1, BMW ATF-3+, MB 236.91, ALLISON C-4, JASO 1A, Toyota Type IV, Nissan Matic-S

#### Application:

Black Bulls is a top-quality synthetic multi vehicle transmission fluid with special friction modification formulated with synthetic base stocks and special performance additive system. Expressly recommended for automatic and semi-automatic transmissions used in passenger cars and commercial vehicles, operating under severe service conditions.

| CHARACTERISTICS          | TEST METHOD | TYPICAL VALUE    |
|--------------------------|-------------|------------------|
|                          |             | <b>DEXRON VI</b> |
| Density at 15 °C, Kg/L   | ASTM D-1298 | 0.845            |
| Viscosity at 40 °C, cSt  | ASTM D-445  | 48.0             |
| Viscosity at 100 °C, cSt | ASTM D-445  | 6.6              |
| Viscosity Index          | ASTM D-2270 | 155              |
| Flash Point, COC, °C     | ASTM D-92   | 208              |
| Pour Point, °C           | ASTM D-97   | -42              |
| Color                    | Visual      | Red              |

#### Key Features:

- Excellent protection against corrosion and oxidation.
- Excellent low temperature fluidity, seal compatibility
- Good Foam control, shear stability and anti-wear properties.
- Good Antirust properties and extra fuel economy benefits.
- Can be used for applications requiring Dexron II, Dexron III H and Type IV transmissions