



## CONTINUOUSLY VARIABLE TRANSMISSION FLUID

### ATF CVT Fluid

#### Performance profile:

GM/SATURN DEX-CVT, DAIHATSU AMIX CVTF-DC, MB CVT28,236.20, FORD CVT23/30, BMW 8322 0 136 376, AUDI/VW TL 52180, NISSAN NS-1/2/3, TOYOTA TC, FE, LEXUS FE, SUZUKI CVTF 3320 , DODGE NS-2 , CVTF+4

#### Application:

Black Bulls is a top-quality transmission fluid with in continuously variable transmission category. New concepts of friction modification formulated with highly refined base stocks and specially selected complete additive system. This multi-vehicle fluid has been developed to be used in all belt and chain CVT's. It's provide smoother, consistent all-weather step-less shifting and all-round lubrication protection of transmission components to help extend transmission service life.

CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
		CVT
Density at 15 °C, Kg/L	ASTM D-1298	0.8490
Viscosity at 40 °C, cSt	ASTM D-445	34.05
Viscosity at 100 °C, cSt	ASTM D-445	7.19
Viscosity Index	ASTM D-2270	184
Flash Point, COC, °C	ASTM D-92	220
Pour Point, °C	ASTM D-97	-51
Color	Visual	Red

#### Key Features:

- Good stability and oxidation stability
- Good low temperature fluidity, seal compatibility
- Foam control, corrosion and anti wear properties.
- Antirust properties and detergent inhibiting qualities.
- Outstanding metal to metal friction performance.
- Improved anti-shudder durability.

