



SYNORA 15W-40 SN

Synthetic Blend PCEO

PERFORMANCE LEVELS: Meets and Exceeds

API SN, ILSAC GF-6

Black Bulls **Synora** Semi-synthetic motor engine oil is our most advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high performance gasoline engines.

Suitable for all gasoline, diesel, gas or dual fuel engines of passenger cars, light duty commercial and off-road SUV's requiring API SN service category with SAE 15W-40 viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean providing reduced engine wear and improving performance.

Typical properties

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUE
SAE VISCOSITY GRADE			15W-40
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D-1500	L2.5
DENSITY @29.5°C	g/mL	ASTM D-4052	0.8738
KINEMATIC VISCOSITY @100°C	cSt	ASTM D-445	14.8
KINEMATIC VISCOSITY @40°C	cSt	ASTM D-445	Report
VISCOSITY INDEX	NA	ASTM D-2270	136
CORRECTED FLASH POINT	°C	ASTM D-92	228
HOMOGENEITY/MISCIBILITY	NA	ASTM D-6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D-97	-30
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D-2896	6.9

Note: Product properties and physical characteristic provided above are typical figures of current production and shown as guidance only and do not constitute any form of guarantee.





Advantages

- Fully & Semi-Synthetic formulation
- Improved oxidation resistance
- Protection from piston deposits
- Superior wear and corrosion protection
- Excellent fuel economy and energy efficiency
- Helps quick engine start in cold climatic conditions
- Enhances the performance of emission controls system

Applications

- For modern gasoline, diesel, gas and Dual fuel engines or as recommended by the OEM
- Serves best for high-end German, Japanese, Korean cars and buses wherever a lubricant of this grade recommended by the OEM.
- Suitable for all engines requiring SN service category and SAE 15W40 viscosity multi-grade engine oil.

