Black Bulls Grease & Lubricants Manufacturing LLC.



Technical data sheet Engine oil

SYNORA 5W-40 SN

Fully Synthetic PCEO

PERFORMANCE LEVELS: Meets and Exceeds

API SN, ACEA A3/B4, MB 229.3, PORSCHE A40, RENAULT RN 0710/0700, VW 502.00 / 505.00

Black Bulls SYNORA Fully synthetic motor oil is our most advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high-performance engines.

Suitable for all gasoline fuel engines of passenger cars, light duty commercial vehicles, and off-road SUV's requiring API SN with 5W-40 viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean, providing reduced engine wear and improving performance.

Typical properties

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE			5W-40
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D-1500	L3.0
DENSITY @20°C	g/mL	ASTM D-4052	0.8602
KINEMATIC VISCOSITY @100°C	cSt	ASTM D-445	14.71
KINEMATIC VISCOSITY @40°C	cSt	ASTM D-445	Report
VISCOSITY INDEX	NA	ASTM D-2270	160
CORRECTED FLASH POINT	°C	ASTM D-92	220
HOMOGENEITY/MISCIBILITY	NA	ASTM D-6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D-97	-36
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D-2896	10.2

Note: Product properties and physical characteristic provided above are typical figures of current production and shown as guidance only and do not constitute any form of guarantee.



1

Black Bulls

Grease & Lubricants Manufacturing LLC.



Technical data sheet Engine oil

Advantages

- Fully Synthetic formulation.
- Environment friendly.
- Keeps your engine like a factory clean.
- Superior wear and corrosion protection.
- Excellent fuel economy and energy efficiency.
- Longer drain intervals and smooth running of engines.
- Helps quickly start in cold weather

Applications:

- For modern gasoline, fuel engines or as recommended by the OEM.
- Serves best for high-end Japanese, Korean cars and light vehicles wherever a lubricant of this grade recommended by the OEM.
- Suitable for all engines requiring API SN, API SM and 5W-40 viscosity.

