Black Bulls

Grease & Lubricants Manufacturing LLC.



Technical data sheet Engine oil

SYNORA Plus 10W-30 SP

Fully Synthetic PCEO

PERFORMANCE LEVELS: Meets and Exceeds

API SP, ACEA A3/B4, MB 229.3

Black Bulls **Synora Plus** Semi-synthetic motor engine oil is our most advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high performance gasoline engines.

Suitable for all gasoline, diesel, gas or dual fuel engines of passenger cars, light duty commercial and off-road SUV's requiring API SP service category with SAE 10W-30 viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean providing reduced engine wear and improving performance.

Typical properties

UNIT	TEST METHOD	TYPICAL VALUE
		10W-30
NA	VISUAL	B&C
NA	ASTM D-1500	2.5
g/mL	ASTM D-4052	0.8706
cSt	ASTM D-445	11.35
cSt	ASTM D-445	Report
NA	ASTM D-2270	140
°C	ASTM D-92	222
NA	ASTM D-6922	Pass
NA	VISUAL	Agreeable
°C	ASTM D-97	-33
mg KOH/g	ASTM D-2896	7.3
	NA NA g/mL cSt cSt NA °C NA NA °C	NA VISUAL NA ASTM D-1500 g/mL ASTM D-4052 cSt ASTM D-445 cSt ASTM D-445 NA ASTM D-2270 °C ASTM D-92 NA ASTM D-6922 NA VISUAL °C ASTM D-97

Note: Product properties and physical characteristic provided above are typical figures of current production and shown as guidance only and do not constitute any form of guarantee.



Black Bulls

Grease & Lubricants Manufacturing LLC.



Technical data sheet Engine oil

Advantages

- Fully & Semi-Synthetic formulation
- Improved oxidation resistance
- Protection from piston deposits
- Superior wear and corrosion protection
- Excellent fuel economy and energy efficiency
- Helps quick engine start in cold climatic conditions.
- Enhances the performance of emission controls system.

Applications

- For modern gasoline, diesel, gas and Dual fuel engines or as recommended by the OEM.
- Serves best for high-end German, Japanese, Korean cars and buses wherever a lubricant of this grade recommended by the OEM.
- Suitable for all engines requiring SP service category and SAE 10W30 viscosity multi-grade engine oil.

