



## SYNORA Plus 5W-30 SP

**Fully Synthetic** PCEO

**PERFORMANCE LEVELS: Meets and Exceeds**

API SP, ILSAC GF-6

**Black Bulls SYNORA Fully synthetic motor oil.** our most advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high-performance engines.

Suitable for all gasoline fuel engines of passenger cars, light duty commercial vehicles, and off-road SUV's requiring API SP with 5W-30 viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean providing reduced engine wear and improving performance.

### Typical properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE			5W-30
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D-1500	2.5
DENSITY @20°C	g/mL	ASTM D-4052	0.851
KINEMATIC VISCOSITY @100°C	cSt	ASTM D-445	11.81
KINEMATIC VISCOSITY @40°C	cSt	ASTM D-445	70.89
VISCOSITY INDEX	NA	ASTM D-2270	165
CORRECTED FLASH POINT	°C	ASTM D-92	214
COLD CRANKING SIMULATOR, -30°C	cP	ASTM D-5293	5792
HOMOGENEITY/MISCIBILITY	NA	ASTM D-6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D-97	-36
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D-2896	7.4

Note: Product properties and physical characteristic provided above are typical figures of current production and shown as guidance only and do not constitute any form of guarantee.

### Advantages:

- Fully Synthetic formulation.
- Environment friendly.
- Keeps your engine like factory clean.
- Superior wear and corrosion protection.
- Excellent fuel economy and energy efficiency.
- Longer drain intervals and smooth running of engines.
- Helps quick cold weather starting

### Applications:

- For modern gasoline, fuel engines or as recommended by the OEM.
- Serves best for high-end Japanese, Korean cars and light vehicles wherever a lubricant of this grade recommended by the OEM.
- Suitable for all engines requiring API SP, API SN and API SM, series and 5W-30 viscosity.

