



## SYNORA Plus 5W-40 SP

Fully Synthetic PCEO

PERFORMANCE LEVELS: Meets and Exceeds

API SP, ILSAC GF-6, ACEA A3/B4, MB 229.3, RN 0710/700, VW 502.00/505.00

**Black Bulls SYNORA Plus Fully synthetic motor oil.** our most advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high-performance engines

Suitable for all gasoline, gas or dual fuel engines of passenger cars, light duty commercial vehicles, and off-road SUV's requiring API SP with 5W-40 viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean, providing reduced engine wear and improving performance.

### Typical properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE			5W-40
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D-1500	2.0
DENSITY @20°C	g/mL	ASTM D-4052	0.8490
KINEMATIC VISCOSITY @100°C	cSt	ASTM D-445	14.65
KINEMATIC VISCOSITY @40°C	cSt	ASTM D-445	Report
VISCOSITY INDEX	NA	ASTM D-2270	169
CORRECTED FLASH POINT	°C	ASTM D-92	226
HOMOGENEITY/MISCIBILITY	NA	ASTM D-6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D-97	-42
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D-2896	7.2

Note: Product properties and physical characteristic provided above are typical figures of current production and shown as guidance only and do not constitute any form of guarantee.

### Advantages:

- Fully Synthetic formulation.
- Environment friendly.
- Keeps your engine like factory clean.
- Superior wear and corrosion protection.
- Excellent fuel economy and energy efficiency.
- Longer drain intervals and smooth running of engines.
- Helps quick cold weather starting.

### Applications:

- For modern gasoline, diesel, gas and dual fuel engines or as recommended by the OEM.
- Serves best for high-end German, Japanese, Korean cars and buses wherever a lubricant of this grade recommended by the OEM.
- Suitable for all engines requiring API SP Oils such as SP, SN series and 5W-40 viscosity.

